




# SEVEN

SMART 7KW CHARGER

# SEVEN



## Simply Smart.

A smart 7kW EV charger built with high reliability and low cost in mind. A smart 7kW charger with a variable output from 6 to 32A. With built in load management, PEN fault & RCD protection and simplified installation with no need for the front case to be removed. Its sleek matte black finish is complimented by an impressive feature set and smart tariff integrations, to ensure you're fully in charge at all times

3

**YEAR WARRANTY**  
Offering full cover and support service.

2

**CHARGER OPTIONS**  
Tethered with 5m cable or universal socket.

1

**FREE TO USE APP**  
Charge scheduling, history, authentication and more...



### Load Balancing

Hard wired dynamic load balancing with CT provided in box. Never overload your main supply



### Robust Casing

Robust IK10 rated ABS casing. Chargers built to last in any environment



### RFID

Built-in RFID reader for easy charge card registration and local charge authorisation



### Cable Lock

Turning untethered chargers into tethered at the touch of a button. Secure your cable.



### Anti-Tamper

Magnetic anti-tamper switch built in for case open detection and emergency cut-off



### OCPP 1.6

OCPP 1.6 compliant for easy integration with plethora back-end service providers



### Universal Socket

Universal Type 2 socket or tethered 5 metre Type 2 cable built in for the same price.



### Secure

Compliant with all UK smart charging standards & encrypted bluetooth, WiFi & RFID.



### PEN Protection

Simplified installation and reduced project costs, through built in OPEN protection



### Solar Integration

Our chargers monitor your solar export allowing you to charge for free with a single CT

## VCHRGD Home.



At VCHRGD we think EV charging should be easy, and the VCHRGD Home App is designed to give you complete control over your charging, at home or on the go. The VCHRGD Home app is free to download and free to use. Complete with a comprehensive set of features allowing you to: schedule, authorise, monitor and track your charge sessions over time.

<p><b>Solar Charging</b> Solar only, solar + scheduling and adjustable export sensitivity and grid load all in app</p>	<p><b>Scheduling</b> Set your charger up to charge when it's cheapest for you, smart tariff integration and more</p>	<p><b>RFID</b> Easily register new tap &amp; charge cards for local charge authorisation &amp; security</p>
<p><b>Cable Lock</b> Turning untethered chargers into tethered at the touch of a button. Secure your cable easily</p>	<p><b>Charge History</b> Track your charging history, costs timings, average power output and visual schedules</p>	<p><b>Live Chat</b> Built in Live Chat feature, putting our UK technical team in the palm of your hand</p>



## Smart charging as standard.

Choice is important so we're also available on...

**MONTA**  
**POWERVERSE**





## Specifications.

Available in tethered complete with a 5m length cable and European Standard Type-2 connector, or untethered with a universal Type-2 Socket, it's an ideal choice for domestic charging. Integral O-PEN protection, means that no additional earth rod is required, and simple connections make the installation process fast and efficient. WiFi & Bluetooth Connectivity allow for remote authorisation, charge scheduling and diagnostics via mobile app and online portal.

### Features.

- Single Phase, 32A 7kW Charger
- 5m Cable with Type 2 Connector
- App Controlled Access & Scheduling
- Wall or Stand Mounted
- Compact Design - 340 x 200 x 130mm
- OCPP 1.6 JSON

### Protection.

- Integral Welding Detection
- Integral PEN Protection
- Robust Weatherproof Casing IP55/IK10

### Connectivity.

- WiFi (IEEE 802.11bgn) @2.4 Ghz
- Bluetooth 4.2

### Tethered



### Untethered



Electrical Characteristics	
Charger Type	Mode 3 (IEC61851-1)
Nominal Supply	Single phase 230V, 50/60Hz
Charging Power	Up to 32A (7kW)
Over Current Protection	40A
Current rating	5 Steps Adjustable (6A to 32A)
Standby Power Consumption	<2.5W
Earth Leakage Protection	AC 30mA + DC 6mA
PEN Protection	PE Current (BS7671:722.411.4.1 Ident v)
Supply Connection	L, N + PE

Connectivity Specifications	
WiFi	(IEEE 802.11bgn) @2.4Ghz
	WPA-2
Connection security	Transport Layer Secure Encryption HTTPS

## Specifications.

Mechanical Features	
Connector	Type 2 IEC62196
Mounting	Wall or Pedestal
Dimension (mm)	200(L) 340(H) 136(D)
Weight	4kg approx. (excl. charging cable) 5kg w/ cable
IP Class/IK Class	IP55 / IK10

Safety & Operational Ratings	
Status	LED Indication
Operating Ambient Temperature	-25°C to 50°C
Relative Humidity	5% - 90%
Atmospheric Pressure	80kPA - 110kPA
EMC Compliance	EN55011 Class B
Integral Protection	Under & Over Voltage & Current
	6mA DC Leakage Detection
	PEN Fault Protection
	Undergrounded
Current Measurement Accuracy	≥2% Accuracy

Compliance & Certification	
Certification	IEC61851-1:2017
	IEC61851-22-2:2018
	LVD 2014/35/EU
	BS7671: 2018
	EN61000-3-11
	EN61000-2-2
	EMCD 2014/30/EU
Protocol	OCPP 1.6
CE Certified	YES

